


GS-2046, GS-2646 and GS-3246

- The solid steel deck platform has a **slip-resistant surface**.
- Heavy duty steel guardrails **maximize durability**.
- **Lubrication-free, service-free pivot points**.
- **Built-in lanyard attachment points** are provided.
- The ergonomic Joystick Controller operates from the platform or the ground.
- **Low noise level** allows operation in quiet work environments.



Specifications

Model	GS-2046		GS-2646		GS-3246	
	US	Metric	US	Metric	US	Metric
Working height	27 ft	8.2 m	32 ft	9.75 m	38 ft	11.58 m
Platform height	21 ft	6.37 m	26 ft	7.9 m	32 ft	9.75 m
Ⓐ Height - stowed (guardrails lowered)	71 3/4 in	182.25 cm	78 1/2 in	199.4 cm	83 3/4 in	212.73 cm
Ⓐ Height - stowed (guardrails)						
ANSI, CSA	78 1/2 in	199.39 cm	85 3/8 in	216.9 cm	90 1/2 in	229.87 cm
CE	82 7/8 in	210.44 cm	89 3/4 in	228 cm	94 7/8 in	241.05 cm
Ⓑ Height - stowed (platform)	39 1/4 in	99.7 cm	46 in	116.84 cm	51 1/4 in	130.18 cm
Ⓒ Length - stowed	96 in	243.84 cm	96 in	243.84 cm	96 in	243.84 cm
Ⓓ Width	46 in	116.84 cm	46 in	116.84 cm	46 in	116.84 cm
Ⓔ Wheelbase	72 7/8 in	185.1 cm	72 7/8 in	185.1 cm	72 7/8 in	185.1 cm
Ⓕ Ground clearance - at machine center	4 in	10.16 cm	4 in	10.16 cm	4 in	10.16 cm
Ⓖ Ground clearance - pothole guards deployed	7/8 in	2.22 cm	7/8 in	2.22 cm	7/8 in	2.22 cm
Ⓗ Platform length-stowed	89 in	226.1 cm	89 in	226.1 cm	89 in	226.1 cm
Platform length-extended	128 1/4 in	325.75 cm	128 1/4 in	325.75 cm	128 1/4 in	325.75 cm
Ⓙ Platform width	45 5/8 in	116.01 cm	45 5/8 in	116.01 cm	45 5/8 in	116.01 cm
Lift capacity ANSI, CE	1,200 lbs	544 kg	1,000 lbs	454 kg	700 lbs	316 kg
CSA	1,200 lbs	544 kg	1,000 lbs	454 kg	500 lbs	227 kg
Extension deck lift capacity	250 lbs	113 kg	250 lbs	113 kg	250 lbs	113 kg
Turning radius outside	91 3/4 in	233 cm	91 3/4 in	233 cm	91 3/4 in	233 cm
Turning radius inside	zero		zero		zero	
Power source	24V (4 6V 245AH batteries) (all models)					
Drive speed - stowed	2.2 mph	3.5 km/h	2.2 mph	3.5 km/h	2.2 mph	3.5 km/h
Drive speed - raised	0.5 mph	0.7 km/h	0.5 mph	0.7 km/h	0.5 mph	0.7 km/h
Raise/lower speed	30/28 sec		30/24 sec		57/40 sec	
Controls	proportional		proportional		proportional	
Tires (solid rubber)	15x5x8 in 38.10x12.7x20.3 cm (all models)					
Gradeability	30%	30%	30%	30%	25%	25%
Drive	dual front wheel		dual front wheel		dual front wheel	
Multiple disc brakes	dual rear wheel		dual front wheel		dual front wheel	
Weight	4,270 lbs	1,937 kg	4,530 lbs	2,055 kg	5,090 lbs	2,309 kg

- High angle steering provides **excellent maneuverability**.
- Swing-out battery box and power module allow **easy access to components**.
- Variable speed motor **extends battery and motor life** by using only the energy needed to do the required work.

Standard Features

- Proportional controls for lift and drive functions
- AC outlet in platform
- Multiple disk brakes provide smooth deceleration
- Manual platform lowering valve
- Tilt sensor with an audible alarm
- Pothole guards
- Emergency stop switches at both platform and ground controls
- Automatic 25 amp battery charger
- Manual brake release
- Non-marking tires
- Hour meter

Options and Accessories

- Automotive horn
- Motion alarm
- Swing platform gate
- Air line to platform
- Dual flashing beacons
- Power inverter

Standards Compliance

- ANSI/SIA A92.6
- CSA CAN3-B354.2-M82
- CE compliance option